



Grade 30, Proof Coil Chain - Reels



- Excellent Low Carbon Steel Chain for General Purpose Applications
- Frequently Used for Swing Sets, Borders, Crowd Control and Other General Applications
- Standard Finish: Zinc Plated or Polycoated Yellow
- Hallmarking: "C3" and "USA" on 5/16" and Larger
- Proof Tested
- Design Factor: 4 to 1
- Packaged on Reels, Order Unit is "Each"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Zinc Plated		Yellow Polycoat		Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
	Catalog No.	UPC No. 020418	Catalog No.	UPC No. 020418							
3/16 in	0725027	064982	PD0725027	184642	0.21 in	0.95 in	0.34 in	800 lb	100 ft	10.75	38 lb
1/4 in	0722127	183270	—	—	0.26 in	1.20 in	0.45 in	1300 lb	65 ft	10.75	41 lb
1/4 in	—	—	PD0722127	183393	0.26 in	1.20 in	0.45 in	1300 lb	60 ft	10.75	36 lb
5/16 in	0722227	183287	—	—	0.31 in	1.27 in	0.47 in	1900 lb	60 ft	10.75	50 lb
3/8 in	0722327	183294	—	—	0.37 in	1.36 in	0.57 in	2650 lb	35 ft	10.75	44 lb

Marine Proof Coil Chain - Drums



- Excellent Low-Carbon Steel Chain Made with A Shorter Link Length Than Standard Proof Coil
- Proof Tested
- Hallmarking: "C3"
- Design Factor: 4 to 1
- Packaged in Drums, Order Unit is "Feet"
- Made in the USA
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Self-Colored		Hot Galvanized		Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
	Catalog No.	UPC No. 020418	Catalog No.	UPC No. 020418							
1/4 in	0128102*	182969	0128132	170645	0.28 in	1.00 in	0.50 in	1300 lb	800 ft	12	584 lb
5/16 in	—	—	0128232	170652	0.34 in	1.10 in	0.50 in	1900 lb	550 ft	11	561 lb
3/8 in	0128302*	182983	0128332	170669	0.41 in	1.23 in	0.62 in	2650 lb	400 ft	9.7	640 lb
1/2 in	—	—	0128432	170676	0.53 in	1.50 in	0.81 in	4500 lb	200 ft	7.8	554 lb

* These Items are Made to Order