



Chain Connector Clamps

- "GX" Style Chain Connector Clamp
- Clamp Comes Fitted with Chain Connector in Place of the Clamp Shackle
- Use of This Clamp Increases the Flexibility of Multiple Leg Chain Slings
- Clamp is Made of Drop Forged and Heat Treated Alloy Steel
- Minimum WLL of at Least 10% of the Maximum WLL

Catalog No.	UPC No. 020418	Style	Grip Range	Working Load Limit (Metric Tons)	Weight Each
6423900	175947	Regular "GX"	1/16 to 5/16 in.	1/2 t	4.50 lb
6423905	175954	Regular "GX"	1/16 to 3/4 in.	1 t	9.00 lb
6423805	177378	Short Leg Structural "GX"	1/16 to 3/4 in.	1 t	10.00 lb



GX Rubber Pad (Non-Marring) Clamps

- Has A Rubber Covered Pad
- Cam of Relatively Smooth Metal Conditioned to Grip Tightly
- Should Be Used for Lifting Smooth Polished Plates and/or Hard Plates Over 43 Rockwell C/400 Brinnell
- Lifts Heavy Plates with Minimum Marring
- Clamps Are 100% Proof Tested and Certificate of Test Supplied with Each Clamp
- Minimum WLL of at Least 10% of the Maximum WLL

Catalog No.	UPC No. 020418	Grip Range	Working Load Limit (Metric Tons)	Weight Each	Shelf Pack
6423600	175916	1/16 to 3/8 in.	1/2 t	6.00 lb	-
6423605	175923	1/16 to 5/8 in.	1 t	22.00 lb	1



Repair Kits for "GX" Rubber Pad Clamps

- Replacement Part Kits for All "GX Rubber Pad" Style Clamps
- Kits Contain All Necessary Parts for Shackle or Cam/Pad Replacement
- Shackle Kit Includes: 1 Shackle, 1 Radius Link, 1 T-Spring, 2 Connecting Links, 1 Radius Link Pin, 3 Linkage Rivets, 2 Sel-Locs
- Note: Shackle Kit is Supplied Pre-Assembled for Easier Installation
- Cam/Pad Kit Includes: 1 Cam, 1 Rubber Pad, 1 Cam Pin, 1 Pad Pin, 1 T-Spring, 1 Rivet, 4 Sel-Locs, 3 Screws
- Note: The Cam and Pad Should Be Replaced at the Same Time



Catalog No.	UPC No. 020418	Part Name	For Use With Clamp Capacity	Weight Each
6506060	210280	Shackle Kit	1/2 TON	1.20 lb
6506061	210297	Cam/Pad Kit	1/2 TON	1.00 lb
6506070	210266	Shackle Kit	1 TON	1.50 lb
6506071	210273	Cam/Pad Kit	1 TON	1.50 lb