



MISCELLANEOUS



310C Conversion Kit

- Filler Plate: 1-1-8" x 3-3/8" (29 mm x 86 mm)
 Strike: 1-11/16" x 2-1/4" (43 mm x 57 mm)
 Materials: Brass
 Finishes: US10B, US26D
 Notes:
 - Packed with filler plate, strike and fasteners
 - Change door from Roller Latch to Push/Pull Latch



322V Wrought Door Knocker with Viewer (115°)

- Certification: Meets ANSI A156.16 for L03163
 Size: 2-3/16" x 3-1/4" (56 mm x 83 mm)
 Materials: Brass
 Finishes: US3, US4, US10, US26D
 Fasteners: Three (3) #6 x 3/4" TPHSMS
 Engraving: Available up to four characters
 Notes: Requires 1/2" (13 mm) hole for viewer



334V Door Knocker with Viewer (115°)

- Certification: Meets ANSI A156.16 for L03163
 Size: 3-9/16" x 6-3/4" (90.5 mm x 171.5 mm)
 Materials: Solid Cast Brass
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners:
 - Two (2) #8 finish washers
 - Two (2) 7-32 x 1-7/8" OHMS for 1-5/8" doors
 - Two (2) 7-32 x 2" OHMS for 1-3/4" doors
 Engraving: Available up to four characters



1755 115° Door Viewer

- Certification: Meets ANSI A156.16 for L03223
 Materials: Brass
 Finishes: US3, US4, US5, US10A, US15, US15A, US26, US26D
 Door Thickness: 1-3/8" - 2-1/8" thick, adjustable
 Notes:
 - For doors up to 2-1/8" (54 mm) thick, adjustable
 - Requires 1/2" (13 mm) hole for viewer
 - Tamper resistant
 - 90 minute fire-rated
 - One-way viewer