



MISCELLANEOUS



274B

Door Guard Protection Plate


- Size: 1-1/8" x 1" x 1/2" (28.5 mm x 25 mm x 12.5 mm)
 Materials: Brass
 Finishes: US3, US4, US10, US10B, US15, US26, US26D
 Notes:
 - Used when additional protective plate is required for frame application
 - Mounted with double-sided tape
 - To be used with the 274D



274C

Shim for Door Guard

- Size:
 - 1-1/16" X 1-5/8" (27 mm X 41 mm)
 - 1-1/8" x 1-1/16" (29 mm x 27 mm)
 Thickness: 3/32" (2.3 mm)
 Materials: Black rubber
 Notes: To be used with the 274D



274D

Door Guard

- Certification: Meets ANSI A156.16 for L13041
 Arm Length: 4-1/2" (114 mm)
 Materials: Brass
 Finishes: US3, US4, US10, US10B, US15, US26, US26D
 Fasteners: Three (3) #6 x 1-1/2" OPHWS, four (4) #6 x 3/4" OPHWS, and seven (7) 6-32 x 12" OPHMS
 Notes:
 - Permits door to be slightly opened to allow viewing
 - Hinged bar allows the door guard to be positioned 180 degrees away from the door when not in use
 - Includes door guard protective plate 274B



277D

Door Guard

- Certification:
 - Meets NFPA 80 5.2.13.3
 - Meets NFPA 80 5.2.4.2(9)
 - ADA Compliant Arm
 Size:
 - Base: 2-5/8" H x 1-9/16" W
 - Projection: 2-3/16"
 Materials: Cast zinc
 Finishes: US3, US4, US10B, US15, US26, US26D
 Fasteners:
 - Three (3) #12 x 1- 3/4" FPHSMS
 - Three (3) 12-24 machine screws



300D

Chain Door Check

- Certification: Meets ANSI A156.16 for L02231
 Lengths:
 - 25-1/2" (648 mm) recommended for use with 36" (914 mm) wide door
 - 30-1/2" (775 mm) recommended for use with 42" (1067 mm) wide door
 Base Plate: 1-1/2" x 1-1/2" (38 mm x 38 mm)
 Materials:
 - Cast zinc base
 - Galvanized steel chain
 - EDPM rubber cover
 Finish: US26D
 Fasteners: Ten (10) #8 x 1" FPHSMS
 Notes:
 - Tear resistant grey vinyl cover
 - Can be ordered through door mounting with grommet nut sets at extra charge
 - 440 pound load strength
 - Designed for full size exterior doors