



FLUSH BOLTS & COORDINATING DEVICES



280X Dust Proof Strike

- Certification: Meets ANSI A156.16 for L04021
 Face Plate: 1-7/16" x 2-29/32" x 1/8" depth (37 mm x 74 mm x 3 mm)
 Barrel Diameter: 1" (25 mm)
 Barrel Depth: 2-3/16" (56 mm)
 Plunger Diameter: 3/4" (19 mm)
 Materials: Brass
 Finishes: US3, US4, US9, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Two (2) #8 x 1" FPHWS, two (2) plastic anchors, and spanner wrench
 Notes:
 - Packed unassembled with plate, strike, fasteners, and spanner wrench
 - May be used with carpet or threshold application by omitting face plate
 - Designed for use with the bottom bolt of a flushbolt set
 - Spring loaded plunger returns to floor or threshold level anytime flushbolt is retracted, eliminating the need to clean out the bottom strike



281D Slide Flush Bolt

- Certification: Meets ANSI A156.16 for L04201
 Faceplate: 3/4" x 6" (19 mm x 153 mm)
 Bolt Diameter: 1/2" (13 mm)
 Bolt Throw: 1" (25 mm)
 Bolt Backset: 7/16" (11 mm)
 Strike: 7/8" x 1-3/4" (22 mm x 45 mm)
 Materials: Brass, bronze faceplate with steel components
 Finishes: US3, US4, US5, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Four (4) #6 x 3/4" FPHWS
 Notes: Double action spring design provides automatic holding of bolt in projected or retracted position



282D Manual Flush Bolt

- Certification:
 - Fits ANSI A115 door and frame prep
 - Meets ANSI A156.16 for L14251
 Face Plate: 1" x 6-3/4" (25 mm x 172 mm)
 Bolt Head: 1/2" (13 mm) square
 Bolt Throw: 3/4" (19 mm)
 Standard Rod Length: 12" (305 mm) (center of face to corner of door)
 Bolt Backset: 3/4" (19 mm)
 Mortise Strike: 15/16" x 2-1/4" (24 mm x 57 mm)
 Materials: Brass faceplate with steel components
 Finishes: US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Eight (8) #8 x 3/4" combo screws; eight (8) #8 x 1-1/2" combo screws
 Notes:
 - For use on hollow metal/fire-rated doors
 - Non-handed
 - Bolt head rods are adjustable
 - Sold in increments of two
 - 3 hour fire rating for metal doors up to 4 feet wide by 10 feet tall
 - 282S strike plate bag and 282P bolt head available
 - Specify 282R for optional rod length of 18" (457 mm), 25" (635 mm), or 30" (762 mm) (bolt head not included)

