



LATCHES & PROTECTION PLATES



318S

Roller Latch with Stop

- Certification: Meets ANSI A156.16 for E0911
 Roller Faceplate: 1-7/16" wide x 4-7/16" high x 11/16" angle (37 mm x 111 mm x 18 mm)
 Strike: 1-1/8" x 2-1/4" (29 mm x 57 mm)
 Strike Gauge: 0.171" (4.3 mm)
 Materials: Brass
 Finishes: US3, US4, US10, US10B, US15, US26, US26D
 Fasteners: Two (2) #10 x 1-1/2" FPHWS and two (2) 8-32 x 3/4" FPHMS
- Notes:
- Adjustable spring tension with nylon roller
 - Projection of roller is easily adjusted using screws on faceplate
 - Max projection of the roller is 3/8" (9.5 mm) allowing for variance in door and frame clearance



320R

Roller Catch with Tee Strike


- Certification: Meets ANSI A156.16 for E0910
 Roller Faceplate: 1-1/8" x 2-1/4" (29 mm x 57 mm)
 Strike: 1-1/4" x 2-3/4" x 1/16" thick (32 mm x 70 mm x 1.5 mm)
 Materials: Brass
 Finishes: US3, US4, US10, US10B, US15, US26, US26D
 Fasteners: Four (4) #8 x 1" FPHWS
- Notes:
- Adjustable spring tension with nylon roller
 - Projection of roller is adjusted by turning knurled knob on back of the latch
 - Max projection of the roller is 7/16" (11 mm) allowing for variance in door and frame clearance
 - For use with wood door and frame



321R

Adjustable Ball Catch with Strike

- Roller Faceplate: 1" x 2-1/8" (25 mm x 54 mm)
 Strike: 1-1/2" x 2-1/8" (38 mm x 54 mm)
 Strike Gauge: 0.050" (1.3 mm)
 Materials: Brass with steel ball
 Finishes: US3, US4, US10, US10B, US15, US15A, US19, US26D
 Fasteners: Four (4) #6 FPHWS
- Notes:
- Adjustable threaded barrel compensates for various door clearances
 - Adjustable spring tension
 - For use with wood door and frame



323S

Three-Way Ball Catch

- Certification: Meets ANSI/BHMA 156.9.B13302
 Body: 1/2" W x 2-3/16" H x 1/2" D
 Strike:
 - 3/8" W x 1-3/8" H x 5/8" D
 - Plate type strike
 Materials: Brass with steel balls
 Finish: US26D
- Notes:
- Adjustable spring tension is easily adjusted to suit field conditions
 - Body can be surface applied or mortised

