



WALL STOPS & HOLDERS



256W

Manual Wall Stop & Holder

Certification: Meets ANSI A156.16 for L01351
Base Diameter: 2-1/4" (57 mm)
Base Projection: 3-3/4" (95 mm)
Engaged Projection: 5-11/16" (145 mm)
Keeper: 25/32" x 1-1/2" (20 mm x 38 mm)
Materials: Cast brass with black rubber bumper
Finishes: US3, US10, US10B, US15, US26, US26D
Fasteners: One (1) #10 x 1" OPHWS, one (1) plastic anchor, one (1) 5/16-18 lead anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud

- Notes:
- For use on concrete walls
 - Ideal for interior and exterior applications
 - Heavy duty - for use in high traffic areas
 - Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged
 - Ideal for use with locksets with a projection of 3" (76 mm) or less



260W

Angled Wall Stop

Certification: Meets ANSI A156.16 for L02201
Base: 2-3/16" x 2-15/16" (56 mm x 75 mm)
Projection: 3-21/32" (93 mm)
Materials: Cast brass with black rubber bumper
Finishes: US26D
Fasteners: Three (3) #14 x 1-1/2" FPHWS, three (3) 1/4-20 x 3/4" FPHMS, three (3) plastic anchors, and three (3) 1/4-20 lead anchors

- Notes:
- For use with drywall or concrete walls
 - Sloping design resists vandalism
 - Ideal for use with locksets with a projection of 3" (76 mm) or less



324W

Light Duty Wall Bumper

Certification: Meets ANSI A156.16 for L02031
Base Diameter: 1-1/4" (32 mm)
Projection: 3-1/4" (83 mm)
Tip Diameter: 5/8" (16 mm)
Materials: Cast brass, bronze with white rubber tip
Finishes: US3, US4, US5, US10, US10B, US15, US15A, US19, US26, US26D
Fastener: #10 x 7/8" wood thread

- Notes:
- Replaceable rubber tip available
 - Hex shape near the tip allows usage of a wrench for easier installation