



PULLS - CLOSET/ POCKET/ SLIDING DOOR



22N

Concealed Edge Pull

Certification: Meets ANSI A156.14 for D2801
 Size: 31/32" x 4-1/4" x 3/8" thick (25 mm x 108 mm x 9.5 mm)
 Lever Extension: 2-19/32" (66 mm)
 Materials: Brass
 Finishes: US3, US26D
 Fasteners: Two (2) #6 x 3/4" FPHWS



330D

Pocket Door Latch

Certification: Meets ANSI A156.14 for D0821
 Size: 2-3/4" x 2-1/2" (70 mm x 64 mm)
 Extension of Finger Piece: 1-3/8" (35 mm)
 Materials: Brass
 Finishes: US3, US5, US10B, US15A, US19, US26, US26D
 Fasteners: Two (2) #6 x 5/8" OPHWS
 Notes: For use with 1-3/8" - 1-3/4" (35 mm - 45 mm) door



330L

Pocket Door Privacy Latch

Certification: Meets ANSI A156.14 for D0831
 Size: 2-3/4" x 2-1/2" (70 mm x 64 mm)
 Extension of Finger Piece: 1-3/8" (35 mm)
 Strike Size: 1" x 2-1/4" (25 mm x 57 mm)
 Materials: Brass
 Finishes: US3, US5, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Two (2) #6 x 5/8" OPHWS and two (2) #6 x 3/4" FPHWS
 Notes: For use with 1-3/8" (35 mm) door



330M

Pocket Door Privacy Latch

Certification: Meets ANSI A156.14 for D0831
 Size: 2-3/4" x 2-1/2" (70 mm x 64 mm)
 Extension of Finger Piece: 1-3/8" (35 mm)
 Strike Size: 1" x 2-1/4" (25 mm x 57 mm)
 Materials: Brass
 Finishes: US3, US5, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Two (2) #6 x 5/8" OPHWS and two (2) #6 x 3/4" FPHWS
 Notes: For use with 1-3/4" (45 mm) door



2610

Flush Cup Finger Pull

Overall Diameter: 31/32" (24.5 mm)
 Finger Pull Diameter: 3/4" (19 mm)
 Pull Clearance: 5/16" (8 mm)
 Projection: 1/32" (.8 mm)
 Materials: Solid brass
 Finishes: US3, US4, US5, US10A, US15, US15A, US26, US26D, ABA
 Notes:

- For use on bi-fold, by-pass or pocket applications
- Built-in prong design eliminates the need for screws or brads