

## 4500 Series Mortise

### Grade 1 Mortise Device



#### Applications:

- Heavy duty commercial

#### Certifications:

- BHMA Certified ANSI A156.3 Grade 1
- UL305 Listed for Panic Hardware
- UL/cUL Listed for up to 3 hours for "A" label doors
- UL10C Positive Pressure Rated
- UL10B Neutral Pressure Rated
- Complies with ANSI A117.1 for accessible buildings and facilities



## PRODUCT SPECIFICATIONS

#### TRIM:

- Archer, August, William or Withnell lever with escutcheon (3902, 1-5/8" cylinder with standard cam sold separately)
- Mortise cylinder (1-3/8") with cylinder collar (11/16") x optional pull
- Mortise trim (45MB, 45MC, 45MD, 45MN) does not match center line of other 4500 Series trim (45BE, 45CE, 45DT, 45NL)

#### FUNCTIONS:

- 4501M: MB, 14 - always operable; MC, 08 - key locks/unlocks lever; MD, 02 - pull when device is dogged down
- 4501N: MN, 03 - key retracts latchbolt

#### COVERS:

- Stainless steel, zinc

#### COVER TUBE:

- Aluminum

#### END CAPS:

- Standard end cap (zinc)
- **OPTIONAL** Flush end cap (zinc)

#### DOOR WIDTH:

- 36" (914 mm) field sizeable to 30" (762 mm) panic-rated door and 28" (711 mm) fire-rated door
- 48" (1219 mm) field sizeable to 36" (914 mm) panic- or fire-rated door
- Reference [electrified exit device](#) for door width specifications

#### DOOR THICKNESS:

- 1-3/4" (44 mm) - standard

#### PROJECTION:

- 3" (76 mm) in undogged position
- 2-5/8" (67 mm) in dogged position

#### STILE WIDTH:

- 4-1/2" (114 mm)
- All stile widths are measured from the door edge

#### FASTENERS:

- Wood and machine screws
- Thru-bolts

#### LATCHBOLT:

- 3/4" (19 mm) throw with anti-friction tongue, all stainless steel with auxiliary deadlocking latch

#### PUSH BAR:

- **OPTIONAL** Photoluminescent push bar cover available

#### STRIKES:

- 4-7/8" (124 mm) ASA strike-standard
- Stainless steel with plated rollers included standard with panic devices

#### FINISHES:

- US3, US4, US10, US10B, US26, US26D, US32D

#### DOGGING:

- Hex key dogging standard on panic rated devices
- Cylinder dogging available on panic rated devices, specify "CD" (3902 mortise cylinder with standard cam sold separately)

#### NOTE:

- Recommended to be used on appropriately reinforced doors