

790-911

Swing Clear - Door of Any Material

Material:

- 14 Ga. (0.075" = 1.9 mm) Type 304 Stainless Steel

Finish:

- US32D Satin



PRODUCT SPECIFICATIONS

CLEARANCE:

- 7/32" (5.6 mm) hinge side
- Plus standard lockside clearance

FASTENERS:

- #10-24 x 5/8" S/S Dril-Kwik (R) (metal frame)
- #10-16 x 1-1/4" S/S Type AB (wood door)

LENGTH OPTIONS:

- Standard and Custom

DOOR REINFORCEMENT:

- None required to 200 lbs. Heavier weight use 16-gauge channel.

FRAME REINFORCEMENT:

- None required to 200 lbs. Heavier weight use 16-gauge channel.

FIRE RATING:

- Up to 3 hr. metal and 90 min. wood composite

SPECIAL FEATURES:

- 1/4" (6.3 mm) diameter Stainless Steel Pin
- Dual 6/6 Nylon bearings between each knuckle
- Door edge protection lip (both faces of door)
- Not recommended for doors with a beveled edge on the hinge side
- Wrap-around frame leaf design for easy installation and protection
- Useful for ADA upgrade work

NOTE:

- Any nonstandard length hinge may require a custom hole pattern based on the requested length. Consult Hager Companies to address the field prep for the doors and frames.

PRODUCT SIZE OPTIONS

LENGTH (INCHES)	LENGTH (CM)	SCREWS (DOOR)	SCREWS (JAMB)
79	200.7	19	19
83	210.8	21	21
85	215.9	21	21
95	241.3	23	23
119	302.3	27	27