



ADVANCED CABLE TIES PART NUMBER					A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	F IN (mm)	ANSI/UL 94 MH FLAMABILITY RATING	
AP(R, L)-AM8-9-C					.752 (19.100mm) +/- .020 (.520mm)	.165 (4.200mm) +/- .012 (.300mm)	.213 (5.400mm) +/- .012 (.300mm)	.394 (10.000mm) +/- .017 (.430mm)	.244 (6.200mm) +/- .014 (.360mm)	.205 (5.200mm) +/- .012 (.300mm)	V-2	
					 <p>ADVANCED CABLE TIES – ANCHOR MOUNT</p>							
					COLOR DESIGNATIONS: 9 = NATURAL					MATERIAL: NYLON 6/6 POLYAMIDE		
B	4/27/17	JA	KT	KT	NEW LOGO ADDED.			SHEET 1 OF 1	REV.: B		DRAWING NO.: AM-B	
A	5/13/14	JA	KT	KT	INITIAL RELEASE			DRAWN BY	DATE		CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION			JA	4/27/2017		KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
 THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.