

MOUNTING HOLE CABLE TIES



MOUNTING HOLE CABLE TIES

Secures and positions wire bundles, cables, hoses, etc.
to panels or other surfaces

- Allows for quicker mechanical mounting and reduced cost
- Two styles available

One-Piece Mounting Hole Cable Ties

ACT Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Screw Size	Diameter Inch/mm	Hole Diameter Inch/mm	Per Bag	Per Case
AL-05-30-MH-9-C*	Natural Nylon	5.8/149.2	.138/3.505	.045/1.143	40 lb. 178 n.	#8	1.25/31.7	.175/4.44	100	10,000
AL-05-30-MH-0-C*	UV Black Nylon								100	
AL-07-50-MH-9-M	Natural Nylon	8.0/203.2	.177/4.495	.052/1.320	50 lb. 222 n.	#10	1.75/44.4	.208/5.28	1,000	5,000
AL-07-50-MH-9-C	Nylon								100	
AL-07-50-MH-0-M	UV Black Nylon								1,000	
AL-07-50-MH-0-C	Nylon								100	
AL-11-50-MH-9-C	Natural Nylon	11.5/292.1	.177/4.495	.053/1.346	50 lb. 222 n.	#10	3.00/76.2	.206/5.23	100	5,000
AL-11-50-MH-0-C	UV Black Nylon								100	
AL-14-50-MH-9-C	Natural Nylon	14.5/368.3	.177/4.495	.053/1.346	50 lb. 222 n.	#10	4.00/101.6	.206/5.23	100	5,000
AL-14-50-MH-0-C	UV Black Nylon								100	
AL-14-120-MH-9-C	Natural Nylon	15.7/400.0	.298/7.569	.075/1.905	120 lb. 534 n.	1/4"	4.06/103.1	.256/6.50	100	2,000
AL-14-120-MH-0-C	UV Black Nylon								100	

Tolerance: .xxx = +.005, .xx = +.015 - *5" made in China

Sold in case quantities



2-Piece Assembled Mounting Hole Cable Ties

ACT Part Number	Color & Material	Assembled Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Screw Size	Diameter Inch/mm	Hole Diameter Inch/mm	Per Bag	Per Case
AL-08-120-MH-9-C	Natural Nylon	9.37/238.0	.300/7.620	.076/1.930	120 lb. 534 n.	1/4"	2.06/52.3	.256/6.50	100	3,000
AL-08-120-MH-0-C	UV Black Nylon								100	
AL-18-120-MH-9-L	Natural Nylon	18.92/480.57	.302/7.670	.083/2.108	120 lb. 534 n.	1/4"	5.00/127.0	.256/6.50	50	1,000
AL-18-120-MH-0-L	UV Black Nylon								50	
AL-24-120-MH-9-L	Natural Nylon	25.17/639.32	.302/7.670	.083/2.108	120 lb. 534 n.	1/4"	7.00/177.8	.256/6.50	50	500
AL-24-120-MH-0-L	UV Black Nylon								50	
AL-30-120-MH-9-L	Natural Nylon	31.54/801.12	.302/7.670	.083/2.108	120 lb. 534 n.	1/4"	9.00/228.6	.256/6.50	50	500
AL-30-120-MH-0-L	UV Black Nylon								50	
AL-36-120-MH-9-L	Natural Nylon	37.72/958.09	.302/7.670	.083/2.108	120 lb. 534 n.	1/4"	11.00/279.4	.256/6.50	50	500
AL-36-120-MH-0-L	UV Black Nylon								50	
AL-24-175-MH-9-L	Natural Nylon	25.92/658.37	.340/8.636	.090/2.286	175 lb. 778 n.	1/4"	7.18/182.3	.256/6.50	50	500
AL-24-175-MH-0-L	UV Black Nylon								50	
AL-36-175-MH-9-L	Natural Nylon	37.92/963.17	.340/8.636	.090/2.286	175 lb. 778 n.	1/4"	11.00/279.4	.256/6.50	50	500
AL-36-175-MH-0-L	UV Black Nylon								50	
AL-48-175-MH-9-L	Natural Nylon	49.23/1250.4	.340/8.636	.090/2.286	175 lb. 778 n.	1/4"	14.50/368.3	.256/6.50	50	500
AL-48-175-MH-0-L	UV Black Nylon								50	

Tolerance: .xxx = +.005, .xx = +.015

Sold in case quantities



Patent Pending.
Sold as assembled units only.



ADVANCED CABLE TIES, INC.

245 Suffolk Lane, Gardner, MA 01440
Phone: 800.861.7228 - Fax: 978.630.3999
sales@actfs.com

