


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .125 (3.175mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .020 (.508mm)	F IN (mm) +/- .030 (.762mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING
	MIN IN (mm)	MAX IN (mm)									
AP(R, L)-07-50-CW-0-C	.062 (1.57mm)	1.875 (47.625mm)	7.562 (192.075mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	HB	N/A
AP(R, L)-11-50-CW-0-C	.062 (1.57mm)	3.062 (77.775mm)	11.250 (285.751mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	HB	N/A
AP(R, L)-14-50-CW-0-C	.062 (1.57mm)	4.000 (101.600mm)	14.500 (368.300mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	HB	N/A
AP(R, L)-14-120-CW-0-C	.187 (4.75mm)	4.0625 (103.187mm)	15.093 (383.362mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	HB	N/A
						ADVANCED CABLE TIES – COLD WEATHER SERIES CABLE TIES					
						COLOR DESIGNATIONS: 0 = UV BLACK			MATERIAL: NYLON 6/6 POLYAMIDE		
C	4/29/17	JA	KT	KT	NEW LOGO ADDED						
B	2/22/17	JA	KT	KT	REVISE 14-50 LENGTH			SHEET 1 OF 1	REV.: C		DRAWING NO.: CW-C
A	12/22/14	JA	KT	KT	INITIAL RELEASE			DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION			JA	4/29/17	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.54.2