


Miscellaneous Cam-Alloy Chain Slings Types Single Adjustable



Style A




Style B

Standard with 1 foot of chain in short leg.

Chain Size	in.	mm	System	Oblong Master Link				Working Load Limit at 90°		
				Nominal Size Material		Inside Dimensions				
				in.	mm	Width	Length	in.	mm	lb
9/32	7	10	37/64	15	2 1/2	64	5	127	4,300	1,950
3/8	10	10	13/16	21	3	76	6	152	8,800	4,000
1/2	13	10	1/8	29	4	102	8	203	15,000	6,800
5/8	16	10	1/8	29	4	102	8	203	22,600	10,300
3/4	20	10	1/4	32	4	102	8	203	35,300	16,000
7/8	22	10	5/8	41	5 1/4	133	10 1/2	267	42,700	19,400
1	26	8	1/8	48	6	152	12	305	47,700	21,600
1 1/4	32	8	2	51	7	178	14	356	72,300	32,800

Dimensions are approximate. These items are made to order.

Cam-Alloy Chain Slings Single Adjustable Loop



Style A




Style B

Standard with 1 foot of chain in short leg.


Chain Size	in.	mm	System	Oblong Master Link				Working Load Limit at 60°		
				Nominal Size Material		Inside Dimensions				
				in.	mm	Width	Length	in.	mm	lb
9/32	7	10	37/64	15	2 1/2	64	5	127	7,400	3,400
3/8	10	10	13/16	21	3	76	6	152	15,200	6,900
1/2	13	10	1/8	29	4	102	8	203	26,000	11,800
5/8	16	10	1/4	32	4	102	8	203	39,100	17,700
3/4	20	10	5/8	41	5 1/4	133	10 1/2	267	61,100	27,700
7/8	22	10	1/8	48	6	152	12	305	74,000	33,500
1	26	8	2	51	7	178	14	356	82,600	37,900
1 1/4	32	8	2 1/4	57	8	203	16	406	125,200	56,800

For other angles of lift, refer to type "D" sling specifications. Dimensions are approximate. These items are made to order.

Cam-Alloy Chain Slings Double Adjustable



Style A




Style B

Standard with 1 foot of chain in short leg.


Chain Size	in.	mm	System	Oblong Master Link				Working Load Limit at 60°		
				Nominal Size Material		Inside Dimensions				
				in.	mm	Width	Length	in.	mm	lb
9/32	7	10	37/64	15	2 1/2	64	5	127	7,400	3,400
3/8	10	10	13/16	21	3	76	6	152	15,200	6,900
1/2	13	10	1/8	29	4	102	8	203	26,000	11,800
5/8	16	10	1/4	32	4	102	8	203	39,100	17,700
3/4	20	10	5/8	41	5 1/4	133	10 1/2	267	61,100	27,700
7/8	22	10	1/8	48	6	152	12	305	74,000	33,500
1	26	8	2	51	7	178	14	356	82,600	37,900

For other angles of lift, refer to type "D" sling specifications. Dimensions are approximate. These items are made to order.

Cam-Alloy Chain Slings Double Adjustable Loop



Style A



Style B

Standard with 1 foot of chain in short leg.

Chain Size	in.	mm	System	Oblong Master Link				Working Load Limit at 60°		
				Nominal Size Material		Inside Dimensions				
				in.	mm	Width	Length	in.	mm	lb
9/32	7	10	13/16	21	3	76	6	152	11,200	5,100
3/8	10	10	1/8	29	4	102	8	203	22,800	10,300
1/2	13	10	1/4	32	4	102	8	203	39,000	17,700
5/8	16	10	5/8	41	5 1/4	133	10 1/2	267	58,700	26,600
3/4	20	10	1/8	48	6	152	12	305	91,700	41,600
7/8	22	10	2 1/4	57	8	203	16	406	110,900	50,250
1	26	8	2 1/4	57	8	203	16	406	123,900	56,900

For other angles of lift, refer to type "D" sling specifications. Dimensions are approximate. These items are made to order.