

Jacobs® High Torque/High Precision Chucks with Integrated Shank

- High Precision Keyless Drill Chuck - Arbor is Integrated Into the Internal Socket of the Drill Chuck
- This Integrated Design Makes It Impossible for the Arbor and the Drill Chuck to Become Accidentally Separated, Providing a Unit of Greater Rigidity and Precision As a Result of Its Compact Design, Accumulated Run-Out is Reduced to a Minimum
- Self-Tightening Feature Automatically Increases Gripping Force Proportional to Increased Torque to Prevent Tool Shank Slippage. Right Handed Operation Only
- 100% Individually Controlled to Ensure Not to Exceed a Maximum Total Integrated Run-Out of 0.0016 in
- Mounts Available: Morse Tapers, Straight Shanks and R-8



Cat. No.	UPC No.	Packaging	Model No.	Min. Capacity	Max. Capacity	Mount	Closed Length	Open Length	Sleeve Dia.	Product Weight	Shelf Pack Qty.
31406D	095456314061	Boxed	JK 80-MT2	0.000 in	0.315 in	MT2	2.83 in	2.56 in	1.50 in	1.35 lb	1
31407D	095456314078	Boxed	JK 100-MT2	0.000 in	0.394 in	MT2	3.23 in	2.87 in	1.69 in	1.81 lb	1
31408D	095456314085	Boxed	JK 130-MT2	0.039 in	0.512 in	MT2	3.62 in	3.15 in	1.89 in	2.65 lb	1
31409	095456314092	Boxed	JK 130-MT3	0.039 in	0.512 in	MT3	3.62 in	3.15 in	1.89 in	2.47 lb	1
31410	095456314108	Boxed	JK 130-MT4	0.039 in	0.512 in	MT4	3.54 in	3.23 in	1.89 in	3.72 lb	1
31411	095456314115	Boxed	JK 130-R8	0.039 in	0.512 in	R8	3.54 in	3.23 in	1.89 in	3.20 lb	1
31414	095456314146	Boxed	JK 160-MT3	0.118 in	0.630 in	MT3	3.78 in	3.35 in	2.13 in	3.21 lb	1
31415	095456314153	Boxed	JK 160-MT4	0.118 in	0.630 in	MT4	3.78 in	3.35 in	2.13 in	4.29 lb	1
31416	095456314160	Boxed	JK 160-R8	0.118 in	0.630 in	R8	3.78 in	3.35 in	2.13 in	3.79 lb	1

Jacobs® Medium Duty Industrial Chucks

- Drill Chucks for Industrial Use (Medium Duty), Available with Threaded Mounts for Professional Portable Drilling Machines and with Taper Fittings for Stationary Drilling Machines
- Automatic Fitting for Efficient, Fast Change of Tools
- Self-Tightening Mechanism Automatically Increases the Grip in Proportion to the Increase in Torque During Drilling
- Fits Tools of Up to 20mm in Diameter.
- Machine Fitting Via DIN0238 of Jacobs Tapers and UNF Thread Fittings



Cat. No.	UPC No.	Packaging	Model No.	Min. Capacity	Max. Capacity	Mount	Closed Length	Open Length	Sleeve Dia.	Product Weight	Shelf Pack Qty.
33363D	095456333635	Boxed	JK 130 1/2	0.039 in	0.512 in	1/2-20	3.74 in	3.39 in	1.73 in	1.58 lb	1
33362	095456333628	Boxed	JK 130 3/8	0.039 in	0.512 in	3/8-24	3.74 in	3.39 in	1.73 in	1.60 lb	1
33365	095456333659	Boxed	JK 130 J2	0.039 in	0.512 in	2JT	3.74 in	3.39 in	1.73 in	1.16 lb	1
33366	095456333666	Boxed	JK 130 J6	0.039 in	0.512 in	6JT	3.74 in	3.39 in	1.73 in	1.00 lb	1
33364	095456333642	Boxed	JK 130 J33	0.039 in	0.512 in	33JT	3.74 in	3.39 in	1.73 in	1.16 lb	1