




# WireSert Locking

Diameter Thread Pitch

5/8-11

Tang



1.25

Suggested Drill Bit Size 0.6563 (21/32)



ZONE		REV.	REVISIONS DESCRIPTION	DATE	APPROVED

## PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

NATIONAL STOCK NUMBER	5340-00-812-1895	DRAWN	NAME	DATE
MILITARY STANDARD	MS21209-C1020	CHECKED		
TH. STANDARD: ANSI/ASME		ENG APPR.		
ACRONYM: UNC		MFG APPR.		
ROTATION: Right-Hand		Q.A.		
MATERIAL FINISH	Stainless Steel 18-8	COMMENTS:		
PART NUMBER	35L7C-C8JJ-06220-1J			
NEXT ASSY	USED ON			
APPLICATION	DO NOT SCALE DRAWING			



**17-B KENTUCKY AVENUE  
PATERSON, NEW JERSEY 07503  
TEL: 973-684-4010 FAX: 973-684-3095  
email: TechSupport@industrialhardware.com  
www.industrialhardware.com**

SIZE	DWG. NO.	REV.
<b>A</b>		
SCALE: 1:8	WEIGHT: 1.77	SHEET 1 OF 1