


# SwiftSert Free-Running

		REVISIONS			
ZONE	REV.	DESCRIPTION	DATE	APPROVED	



0.328

External Thread Pitch  
3/4-16

Internal Thread Pitch  
M14 x 1.25

Suggested Drill Bit Size



0.6875 (11/16)

## PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

		<b>Internal</b> TH. STANDARD : ISO Metric ACRONYMSpark Plug (ISO) ROTATION: Right-Hand	NAME	DATE
		<b>External</b> TH. STANDARD : ANSI/ASME ACRONYM: UNF ROTATION: Right-Hand MATERIAL FINISH Carbon Steel 12L14	DRAWN	
		PART NUMBER 35L9C-98XU-C14H06-05	CHECKED	
NEXT ASSY	USED ON		ENG APPR.	
			MFG APPR.	
			Q.A.	
APPLICATION	DO NOT SCALE DRAWING		COMMENTS:	



**17-B KENTUCKY AVENUE  
PATERSON, NEW JERSEY 07503  
TEL: 973-684-4010 FAX: 973-684-3095  
email: TechSupport@industrialhardware.com  
www.industrialhardware.com**

SIZE <b>A</b>	DWG. NO.	REV.
SCALE:1:8	WEIGHT:	SHEET 1 OF 1