



CYLINDER, CORE & KEYING - CONVENTIONAL CYLINDERS

Rim Cylinder Accessories



2-639-7058
Long Breakoff Tailpiece
2-3/8" (60 mm)



2-300-0118
Extra Long Breakoff Screws
2-3/8" (60 mm)



2-649-0137
Retaining Cup
Can be used with 45PN, 47PN, and 47RN

Mortise Cylinder Housing



3902
Mortise Cylinder

- Conventional cylinder supplied drilled 6-pin, keyed 5-pin standard
- 3975 standard cam attached and 3972 Adams Rite cam shipped loose in the box
- Thread size is 1.150" x 32 UNS
- Cylinder face diameter is 1.360"
- Supplied with two operating keys
- 1-1/8" (29 mm) standard length, 1-1/4" (31 mm), and 1-5/8" (41 mm) for mortise exit devices
- Other lengths may be available with extended lead time
- **Must specify length, cam, keyway, and keying requirements**



3904
Mortise Dummy

- 1-1/8" (29 mm) length
- 1-1/4" (31 mm) length



3905
Mortise ADA Turn Knob

- 1-1/8" (29 mm) length
- 1-1/4" (31 mm) length

Note: Ships with Schlage "L" Cam; specify if different

Mortise Cylinder Cams



3971
Yale Cam
Radius .722" (18 mm)



3972
Adams Rite Cam
Radius .560 (14 mm)



3973
Standard Cloverleaf
Radius .741" (19 mm)



3974
Marks Cam
Radius .755" (19 mm)



3975
Standard Cam
Radius .723" (18 mm)
For use with Hager exit devices and trim



3976
Schlage L Cam
Radius .637" (16 mm)
For use with Hager mortise locks (all functions)



3977
Sargent/Yale Cam
Radius .733" (18.6 mm)



3978
Corbin/Russwin/Best Cloverleaf
Radius .725" (18.5 mm)

