

# Uninsulated

## FIRE-RATED ACCESS DOOR

Babcock-Davis' UL Listed Uninsulated Access Door is designed for use in fire-rated walls while providing access to critical building components.

### DETAILS

**DOOR** 14 gage Steel, Self-Closing

**FRAME** 16 gage Steel

#### SIZE

- Min: 6 inches by 6 inches
- BUT Max: 24 inches by 72 inches or 48 inches by 48 inches
- BUW/BUP Max: 36 inches by 48 inches

**INSTALLATION** Wall

**FLANGE** Exposed, Drywall Bead or Plaster Bead

#### HINGE

- BUT: Flush Continuous Piano
- BUW/BUP: Concealed Pin

**FINISH** White Powder Coat

**CERTIFICATION** UL listed "B" label for 1-1/2 hours



### ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
<b>BU</b>				<b>X</b>		
	<b>T</b> 1 inch flange <b>W</b> Drywall bead <b>P</b> Plaster Bead	<b>K</b> Knurled latch/ key operated latch bolt  <b>M</b> Mortise lock (1-1/8") prep	<b>Standard Sizes (W x L)</b> 8" x 8"    18" x 18"    24" x 30" 10" x 10"    18" x 24"    24" x 36" 12" x 12"    20" x 30"    24" x 48" 12" x 18"    22" x 22"    30" x 30" 12" x 24"    22" x 30"    32" x 32" 14" x 14"    22" x 36"    36" x 36" 16" x 16"    24" x 24"    36" x 48"		<b>B</b> Galvannealed <b>G</b> Gasketing <b>M</b> Masonry Anchors <b>S</b> Type 304 Stainless Steel	

*Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.*

# Oversized Attic

## FIRE-RATED ACCESS DOOR

The Oversized Attic Access Door allows access into ceilings when over-sized or double door applications are required. The double leaf design, with a removable center mullion, allows objects to clear which may interfere with door openings.

### DETAILS

**DOOR** 18 gage Steel

**FRAME** 16 gage Steel

#### SIZE

- Min: 36 inches by 60 inches
- Max: 48 inches by 60 inches

**INSTALLATION** Wall or Ceiling

**FLANGE** Exposed

**HINGE** Continuous Rod or Piano

**FINISH** Off White Prime Coat

**CERTIFICATION** Warnock-Hersey listed for 2 hours



### ORDER GUIDE

BASE	WIDTH	X	LENGTH	OPTIONS
<b>BFRD</b>		<b>X</b>		
	<b>Standard Sizes (W x L)</b> 36" x 60"    40" x 60"    48" x 60"			<b>C</b> Ceiling Application <b>D</b> Double Door <b>M</b> Mortise Lock (1-1/8") prep <b>S</b> Type 304 Stainless Steel <b>T</b> 3-Hour Rated <b>W</b> Wall Application

*Rough opening is door size. Additional sizes available, call for more information.*