

1173

Five Knuckle
- Plain Bearing -
Standard Weight



Additional Notes:

- *For 1-3/8" door, use 3-1/2" or 4" hinge



PRODUCT SPECIFICATIONS

DESCRIPTION:

- ANSI A8433
- Non-rising removable pin with button tip and plug
- Beveled surface leaf
- Reversible
- Thru-bolts and grommets for wood door applications
- For use on regular weight hollow metal or wood composite doors with hollow metal frames requiring low frequency servicebr />

MATERIAL:

- Steel with Steel pin

FINISHES:

- USP, US10, US10A, US10B, US26D

PRODUCT SIZE OPTIONS

HINGE SIZE (INCHES)	HINGE SIZE (MM)	GAUGE OF METAL	HOLE COUNT	DOOR LEAF SCREW SIZE (MACHINE)	JAMB LEAF SCREW SIZE (WOOD)
3 1/2	89	0.119	6	13/4 x 10 - 24 OH	1/2 x 12 - 24 FH
4*	102	0.129	7	2 x 1/4 - 20 OH	1/2 x 12 - 24 FH
4 1/2	114	0.134	7	2 x 1/4 - 20 OH	1/2 x 1/4 - 20 FH

HINGE SIZE (INCHES)	HINGE SIZE (MM)	DOOR LEAF WIDTH "A" (INCHES)	DOOR LEAF WIDTH "A" (MM)	JAMB LEAF WIDTH "B" (INCHES)	JAMB LEAF WIDTH "B" (MM)	JAMB LEAF OFFSET "C" (INCHES)	JAMB LEAF OFFSET "C" (MM)	JAMB LEAF OFFSET "D" (INCHES)	JAMB LEAF OFFSET "D" (MM)
3 1/2	89	15/8	41	19/16	31	7/16	11.5	11/16	27
4*	102	2 5/16	59	113/16	46	1/2	13	15/16	33
4 1/2	114	2 9/16	65	2	51	1/2	12.5	11/2	38