

4700 SURFACE VERTICAL ROD EXIT DEVICE TEMPLATE FOR EXIT DEVICE CHASSIS (FOR PANIC AND FIRE RATED DEVICES)

(REV: 01)
DWG NO: T-ED00318

THIS SIDE UP FOR LHR DOOR

FOLD AND PLACE ON DOOR EDGE OR STOP FACE

PLACE THIS SIDE ON DOOR

FOLD HERE

(2x)METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS
TRIM OR SEXBOLTS: DRILL 5/16" CLEARANCE HOLE
ON PUSH SIDE, 3/8" HOLE ON PULL SIDE
WOOD: PRE DRILL 1/8" HOLES

FOR TRIM DRILL 1/2" CLEARANCE HOLE.

(2x) METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS
SEXBOLTS: DRILL 5/16" CLEARANCE HOLE ON PUSH SIDE,
3/8" HOLE ON PULL SIDE.
WOOD: PRE-DRILL 1/8" HOLES

DOOR EDGE OR STOP FACE

DOOR

2 1/4"
[57]

1 7/16"
[37]

2 7/8"
[73]

☒ OF DEVICE

40" [1016]
RECOMMENDED HEIGHT MAY BE
DETERMINED BY DESIGN SPEC'S

FINISHED FLOOR

3/8"
[10]

1 3/16"
[30]

19/32"
[15]

AFTER EXIT DEVICE IS CUT AND
MOUNTED, INSTALL END CAP
BRACKET CENTERED ON DEVICE ☒

 HOLE LOCATIONS

PRIMARY DIMENSIONS SHOWN IN INCHES,
DIMENSIONS IN [] ARE MILLIMETERS.

THIS SIDE UP FOR RHR DOOR

